

## DECLARATION OF PERFORMANCE

No. 1/2023 of 19.05.2023  
AVCP SYSTEM: System 4

GS24 65 x 215 x 14mm

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: For wall tiling (as finishing) in interiors and/or exteriors of building structures.

| GENERAL CHARACTERISTICS  | PERFORMANCE PROPERTIES  | HARMONISED TECHNICAL SPECIFICATION |
|--|---|------------------------------------|
| REACTION TO FIRE   | Class A1  | BS EN 14411:2012                   |
| WATER ABSORPTION   | ~ 3%  |                                    |
| THERMAL SHOCK RESISTANCE   | Yes   |                                    |
| EXTERNAL USE DURABILITY  | Yes   |                                    |
| FROST RESISTANCE   | Yes   |                                    |
| DIMENSION <ul style="list-style-type: none"><li>• LENGTH AND WIDTH</li><li>• THICKNESS</li><li>• SQUARENESS</li><li>• SURFACE FLATNESS</li><li>• CURVATURE OF SIDES</li></ul>          | ±2.0% to maximum ±4mm<br>±10%<br>±1.0%<br>±1.5%<br>±1.0%                                      |                                    |
| SURFACE QUALITY  | Minimum 95% of slips should not have visible defects causing deterioration of the appearance. |                                    |
| BONDING STRENGTH/ADHESION <ul style="list-style-type: none"><li>• CEMENT ADHESIVES</li><li>• DISPERSION ADHESIVES</li><li>• REACTIVE RESIN ADHESIVE</li><li>• MASONRY MORTAR</li></ul> | NPD<br>NPD<br>NPD<br>NPD  |                                    |
| RELEVANT TECHNICAL DOCUMENTATION OR SPECIAL TECHNICAL DOCUMENTATION: Not Applicable  |   |                                    |

**The performance of the product(s) identified above is in conformity with the declared values:**

Signed for and on behalf of the manufacturer by:



Jason Hughes, Managing Director

April 2025

Imperial Bricks  
Crowgreaves Farm  
Stableford  
Bridgnorth  
Shropshire  
WV15 5LT

