

## DECLARATION OF PERFORMANCE

No. 1/2023 of 19.05.2023  
AVCP SYSTEM: System 4

HM05 65 x 215 x 14mm

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: For wall tiling (as finishing) in interiors and/or exteriors of building structures.

GENERAL CHARACTERISTICS	PERFORMANCE PROPERTIES	HARMONISED TECHNICAL SPECIFICATION
REACTION TO FIRE	Class A1	BS EN 14411:2012
WATER ABSORPTION	~ 3%	
THERMAL SHOCK RESISTANCE	Yes	
EXTERNAL USE DURABILITY	Yes	
FROST RESISTANCE	Yes	
DIMENSION <ul style="list-style-type: none"><li>• LENGTH AND WIDTH</li><li>• THICKNESS</li><li>• SQUARENESS</li><li>• SURFACE FLATNESS</li><li>• CURVATURE OF SIDES</li></ul>	±2.0% to maximum ±4mm ±10% ±1.0% ±1.5% ±1.0%	
SURFACE QUALITY	Minimum 95% of slips should not have visible defects causing deterioration of the appearance.	
BONDING STRENGTH/ADHESION <ul style="list-style-type: none"><li>• CEMENT ADHESIVES</li><li>• DISPERSION ADHESIVES</li><li>• REACTIVE RESIN ADHESIVE</li><li>• MASONRY MORTAR</li></ul>	NPD NPD NPD NPD	
RELEVANT TECHNICAL DOCUMENTATION OR SPECIAL TECHNICAL DOCUMENTATION: Not Applicable		

**The performance of the product(s) identified above is in conformity with the declared values:**

Signed for and on behalf of the manufacturer by:



Jason Hughes, Managing Director

April 2025

Imperial Bricks  
Crowgreaves Farm  
Stableford  
Bridgnorth  
Shropshire  
WV15 5LT

