

## **DECLARATION OF PERFORMANCE**

No. 1/2023 of 19.05.2023 AVCP SYSTEM: System 4

HM07 65 x 215 x 14mm

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: For wall tiling (as finishing) in interiors and/or exteriors of building structures.

GENERAL CHARACTERISTICS	PERFORMANCE PROPERTIES	HARMONISED TECHNICAL SPECIFICATION
REACTION TO FIRE	Class A1	
WATER ABSORPTION	~ 3%	
THERMAL SHOCK RESISTANCE	Yes	
EXTERNAL USE DURABILITY	Yes	
FROST RESISTANCE	Yes	
DIMENSION		
<ul><li>LENGTH AND WIDTH</li><li>THICKNESS</li><li>SQUARENESS</li><li>SURFACE FLATNESS</li><li>CURVATURE OF SIDES</li></ul>	±2.0% to maximum ±4mm ±10% ±1.0% ±1.5% ±1.0%	BS EN 14411:2012
SURFACE QUALITY	Minimum 95% of slips should not have visible defects causing deterioration of the appearance.	
BONDING STRENGTH/ADHESION		
<ul><li>CEMENT ADHESIVES</li><li>DISPERSION ADHESIVES</li><li>REACTIVE RESIN ADHESIVE</li><li>MASONRY MORTAR</li></ul>	NPD NPD NPD NPD	

The performance of the product(s) identified above is in conformity with the declared values:

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

April 2025

Imperial Bricks Crowgreaves Farm Stableford Bridgnorth Shropshire WV15 5LT

