

DECLARATION OF PERFORMANCE

No. 1/2023 of 19.05.2023
AVCP SYSTEM: System 4

LF06 52 x 490 x 14mm

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: For wall tiling (as finishing) in interiors and/or exteriors of building structures.

| GENERAL CHARACTERISTICS | PERFORMANCE PROPERTIES | HARMONISED TECHNICAL SPECIFICATION |
|--|---|------------------------------------|
| REACTION TO FIRE | Class A1 | BS EN 14411:2012 |
| WATER ABSORPTION | ~ 3% | |
| THERMAL SHOCK RESISTANCE | Yes | |
| EXTERNAL USE DURABILITY | Yes | |
| FROST RESISTANCE | Yes | |
| DIMENSION <ul style="list-style-type: none">• LENGTH AND WIDTH• THICKNESS• SQUARENESS• SURFACE FLATNESS• CURVATURE OF SIDES | ±2.0% to maximum ±4mm ±10% ±1.0% ±1.5% ±1.0% | |
| SURFACE QUALITY | Minimum 95% of slips should not have visible defects causing deterioration of the appearance. | |
| BONDING STRENGTH/ADHESION <ul style="list-style-type: none">• CEMENT ADHESIVES• DISPERSION ADHESIVES• REACTIVE RESIN ADHESIVE• MASONRY MORTAR | NPD NPD NPD NPD | |
| RELEVANT TECHNICAL DOCUMENTATION OR SPECIAL TECHNICAL DOCUMENTATION: Not Applicable | | |

The performance of the product(s) identified above is in conformity with the declared values:

Signed for and on behalf of the manufacturer by:



Jason Hughes, Managing Director

April 2025

Imperial Bricks
Crowgreaves Farm
Stableford
Bridgnorth
Shropshire
WV15 5LT

