

DECLARATION OF PERFORMANCE

No. 1/2023 of 19.05.2023
AVCP SYSTEM: System 4

SM32 65 x 215 x 14mm

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: For wall tiling (as finishing) in interiors and/or exteriors of building structures.

GENERAL CHARACTERISTICS	PERFORMANCE PROPERTIES	HARMONISED TECHNICAL SPECIFICATION
REACTION TO FIRE	Class A1	BS EN 14411:2012
WATER ABSORPTION	~ 3%	
THERMAL SHOCK RESISTANCE	Yes	
EXTERNAL USE DURABILITY	Yes	
FROST RESISTANCE	Yes	
DIMENSION <ul style="list-style-type: none">• LENGTH AND WIDTH• THICKNESS• SQUARENESS• SURFACE FLATNESS• CURVATURE OF SIDES	±2.0% to maximum ±4mm ±10% ±1.0% ±1.5% ±1.0%	
SURFACE QUALITY	Minimum 95% of slips should not have visible defects causing deterioration of the appearance.	
BONDING STRENGTH/ADHESION <ul style="list-style-type: none">• CEMENT ADHESIVES• DISPERSION ADHESIVES• REACTIVE RESIN ADHESIVE• MASONRY MORTAR	NPD NPD NPD NPD	
RELEVANT TECHNICAL DOCUMENTATION OR SPECIAL TECHNICAL DOCUMENTATION: Not Applicable		

The performance of the product(s) identified above is in conformity with the declared values:

Signed for and on behalf of the manufacturer by:



Jason Hughes, Managing Director

April 2025

Imperial Bricks
Crowgreaves Farm
Stableford
Bridgnorth
Shropshire
WV15 5LT

