



BRICK SLIPS

BY IMPERIAL BRICKS

TRACKWALL®

Trackwall® is a versatile A1 fire-rated cement fibre backing board designed for fast, secure installation of decorative brick slips.

Suitable for most MMC builds—including timber, steel frame, modular, and ICF. Trackwall provides a robust, reliable surface. Optional availability on standard or bespoke sizes.

Also optional thermally insulated back panels are available in XPS, EPS & PIR.

Key benefits of building with brick slips and Trackwall®

- Suitable for new build, modular, renovation, commercial or domestic
- Compatible façade systems: aluminium systems or timber
- Upto 60% shorter build times
- Exceptional design flexibility
- More cost-effective than rendering
- A1 Fire Rated
- Lower environmental impact
- Zero maintenance required
- Order direct to site, enhancing lead-time flexibility and productivity



The only system on the market that is trued, squared, and manufactured with CAM precision





Technical Highlights

- Fire classification: A1 non-combustible (EN I3501-I:2007+A1:2009), assessed to EN ISO 1182:2010 & EN ISO 1716
- Thermal conductivity: $\lambda = 0.2166 \text{ W / mK}$ (10°C dry) without brick slip - 0.18
- Density: $\geq 1200 \text{ kg/m}^3$
- Bending strength: $\geq 7 \text{ N/mm}^2$
- Compressive strength: $> 35 \text{ MPa}$ (24h) / $> 40 \text{ MPa}$ (7 days)
- Water & frost resistance: certified to TS EN 12467
- Impact resistance: category I (hard & soft body impact) per EAD 090019-00-0404
- Bond strength: 0.47 N/mm^2 (exceeding EAD requirements)
- Panel thickness: 12mm
- Thermal resistance: $55.4 \times 10^{-3} \text{ m}^2\text{K/W}$



Sizes Available

Full Panel	2396 x 1125mm	2.696 m ² per board
Half Panel	1190 x 1125mm	1.339 m ² per board



YOUR BUILD, OUR PASSION

01746 330 994

brickslips@imperialbricks.co.uk

www.brickslips.imperialbricks.co.uk